



The following tables illustrate the characteristics of the machines of our production, but we are also available to realize special machines to satisfy the more different working requirements.

TORGIM	280	300	310	360	350	400
height over bed mm	280	300	310	360	350	400
width of bed mm	380	380	415	415	415	415
swing in gap mm	750	790	790	880	880	970
Ø spindle hole mm	105	105	133	133	146	146
Spindle speeds RPM	14-1400	14-1400	10-1300	10-1300	8-1020	8-1020
motor power kW	7,5	7,5	11	11	11	11
Distance between centres mm	1500-4000	1500-4000	1500-4000	1500-6000	1500-6000	1500-6000
aproximative net weight kg	2750-3650	2850-3750	3700-5500	3900-5700	3750-5500	4000-5700

TORGIM	400	450	500	280 TL	300 TL	450 TL	500 TL
height over bed mm	400	450	500	280	300	450	500
width of bed mm	415	550	550	380	380	550	550
Swing in gap mm	970	1120	1220	750	790	1120	1220
Ø spindle hole mm	146	160	160	111	111	160	160
spindle speeds RPM	8-1020	8-1000	8-1000	25-1800	25-1800	69-1250	69-1250
Power motor kW	11	15	15	15	15	30	30
distance between centres mm	1500-6000	1500-6000	1500-6000	1500-4000	1500-4000	2000-5000	2000-5000
aproximative net weight kg	4000-5700	6300-9000	6600-9300	3200-4100	3300-4200	7300-9300	7600-9600